



Phone  
+8615959014950  
+8615959042799  
Email  
anna@jdctool.com  
sharon@jdctool.com  
Whatsapp  
+8615959014950  
+8615959042799  
Skype  
Anna Luo  
+86-15959014950



ADD ME ON WECHAT



ADD ME ON WHATSAPP



福州金东诚机电设备有限公司  
FUZHOU JDC EQUIPMENT CO.LTD.

## Company profile

Factory is a professional tools manufacturer with ISO 9001-2000 and CE Certificate, manufacturing machines of shear, folding, bend brake, roller, round bending, metal forming, band saw, shaping, slotting, CNC, rocked arm drills, pressure, pressure machines Plasma laser CNC cutting, mining equipments, tools accessories, mechanical parts and castings. The factory consists of 12 different factories which can provide OEM products. Products with great export quantities are warmly welcomed in Europe and America.

Factory insists to provide "excellent products, competitive prices, heart service" to the customers around the world. We are always with you to develop together.

### Hand Shear

Model	HS-5	HS-6	HS-8	HS-10	HS-12	HS-8
Blade length (mm)	5"	6"	8"	10"	12"	8"
Capacity	Sheet steel 6	6	6	6	6	6
	Flat steel 70x6	70x6	70x6	70x6	70x6	70x6
	Round steel 11	11	13	13	13	13
Packing size (cm)	33x16X33	33x16X33	50X16X44	74X16X44	74X16X44	50X16X44
N.W. / G.W. (kg)	10/11	12/14	17/19	21/23	26/28	18/20



### Guillotine Shear

Model	HS-500	HS-800	HS-1000	HS-1300	GS-1000	GS-1000I	KHS-1000	KHS-1270	TSC-1010
Bed width (mm)	500	800	1000	1300	1000	1000	1000	1270	1010
Max. shearing	1.5	1.5	1.5	1.5	1.0	1.0	1.5	1.5	1.6
Packing Size (mm)	86X25X52	108X25X52	126X25X52	156X25X52	155x100x58	165x103x48	156x105x67	186x105x67	150x105x116
N.W. / G.W. (kg)	37/46	41/55	51/70	70/88	238/295	385/445	456/526	551/618	347/426



### Bar & Section Shear

Model	PBS-7	PBS-8	PBS-9	MS-22	MS-28	MS-32
Capacity	Round steel 22	16	22	20	25	30
	Square steel 20	16	20	20	25	30
	Flat steel 90X14	100x10	90X14	30X10	40X12	40X14
	Angle steel 60X7	40x6	60X7			
	T-steel 60X7	40x6	60X7			
	Plate steel 10	8	10			
Body packing size (cm)	97x36x67	66x28x61	110x36x92	41X37X20	45X24X45	45X24X45
Handle packing size(cm)	154x7x5	120x5x2	154x7x5	154x5x5	154x5x5	154x5x5
N.W. / G.W. (kg)	96/111	45/52	130/158	25/27	34/49	46/52



### Hand Notcher

Model	HN-3	HN-4	HN-3/102
Thickness(m)	1.5	1.5	3
Punches	125X125	152x152	100X100
Angle	90 °	90 °	90 °
Ram stroke (mm)	25	20	30
Packing size (cm)	43x37x44	58x53x52	46X45X76
N.W. / G.W. (k)	35/45	75/85	90/105



### Hand Shear/Foot Shear

Model	Q01-1.5X1500	Q01-1.25X2000	Q1-0.8x2500	Q01-1.5X1000	Q01-1.5X1320
Bed width (mm)	1500	2000	2500	1000	1320
Max. shearing	1.5	1.25	0.8	1.5	1.5
Back gauge range (mm)	0-300	0-300	0-300	0-700	0-700
Packing size (cm)	202X75X119	256X75X119	306x75x119	140x76x115	168x76x115
N.W. / G.W. (kg)	460/530	511/606	595/745	365/418	454/508





## Electric Shearing Machine

Model	Q11-3X1250	Q11-4X1250	Q11-3X1300	Q11-3X1500	Q11-3X2050	Q11-4X2000	Q11-4X2500
Max shearing thickness(m)	3	4	3	3	3	4	4
Max shearing width(mm)	1250	1250	1300	1500	2050	2000	2500
Shearing	2"	2"	3"	3"	2"	3"	3"
No of stroke(per minute)	30	30	20	20	30	20	20
Motor power(kw)	3	4	3	3	4	5.5	5.5
Back gauge(mm)	630	630	350	350	630	350	350
Packing size(cm)	184x103x131	184x103x131	233X136X154	253X136X154	266x116x147	308X156X167	363X156X167
N.W./G.W.(k)	850/945	930/1025	1300/1450	1500/1650	1520/1740	3000/3200	3600/3850



## 3-IN-1 Shear, Brake, Roll

Model	3-IN-1/200	3-IN-1/305	3-IN-1/610	3-IN-1/760	3-IN-1/1016	3-IN-1/1320
Bead width	200 mm	305 mm	610 mm	760 mm	1016 mm	1320 mm
Max. shearing	1.0 mm	1.0 mm	1.0 mm	1.0 mm	1.0 mm	1.0 mm
Max. bending thickness	1.0 mm	1.0 mm	1.0 mm	1.0 mm	1.0 mm	1.0 mm
Max. bending angle	90°	90°	90°	90°	90°	90°
Max. rolling thickness	1.0 cm	1.0 cm	1.0 cm	1.0 cm	1.0 cm	1.0 cm
Min. rolling	29 mm	39 mm	39 mm	39 mm	39 mm	50 mm
Packing size	36x25x30 cm	54x33x49 cm	86x42x66 cm	99x42x66 cm	126x42x66 cm	165x53x76 cm
N.W. / G.W.	17/19 kg	43/50kg	112/128 kg	136/153 kg	226/256 kg	356/398 kg



## Hand Brake

Model	36" Brake	40" Brake	48" Brake	72" Brake	W1.0x305A	W1.0x610A	W1.0x915	W1.5x1220
Capacity	Width 915 mm / 36"	1016 mm / 40"	1220 mm / 48"	1830 mm / 72"	305 mm	610 mm	915 mm	1220 mm
Thickness	1.5 mm	1.2 mm	1.0 mm	0.8 mm	1.0 mm	1.0 mm	1.0 mm	1.5 mm
Angle	0-120°	0-120°	0-120°	0-120°	0-135°	0-135°	0-135°	0-135°
Packing size	123x24x50 cm	134x24x50 cm	153x24x53 cm	217x36x64 cm	50x35x41 cm	82x35x44 cm	113x35x55 cm	158x45x66 cm
N.W. / G.W.	68/75 kg	70/84 kg	76/95 kg	145/180 kg	28/30 kg	43/46 kg	80/90 kg	142/160 kg

## Pan & Box Brake

Model	W2.5X1220A	W2.0X2040A	W2.5X2040A	W2.0X2540A	W2.5X2540A	W2.0X3050A	W1.2X3700A	W0.8X4000A
Capacity	Width 1220 mm / 48"	2040 mm / 80"	2040 mm / 80"	2540 mm / 100"	2540 mm / 100"	3050 mm / 120"	3700 mm / 146"	4000 mm / 157"
Thickness	2.5 mm / 12Ga	2.0 mm / 14Ga	2.5 mm / 12Ga	2.0 mm / 14Ga	2.5 mm / 12Ga	2.0 mm / 14Ga	1.2 mm / 20Ga	0.8 mm / 22Ga
Angle	0-135°	0-135°	0-135°	0-135°	0-135°	0-135°	0-135°	0-135°
Packing size (cm)	170x75x96 cm	254x76x102	253x75x101	300x76x102	300x76x102	360x76x102	425x85x12	470x90x120
N.W. / G.W. (kg)	495/575 kg	960/1070 kg	1060/1170 kg	1115/1245 kg	1225/1360 kg	1435/1605 kg	2450/2670 kg	2700/2950 kg

## Magnetic Bending Machine

Model	EB625	EB1000	EB1250	EB2000	EB2500	EB3200
Max. bending length	625 mm / 2'	1000 mm / 3'	1250 mm / 4'	2000 mm / 6'	2500 mm / 8'	3200 mm / 10'
Max.	1.6 mm / 3 Ton	1.6 mm / 4.5 Ton	1.6 mm / 6 Ton	1.6 mm / 9 Ton	1.6 mm / 12 Ton	1.2 mm / 18Ga
Clamping	30%	30%	30%	30%	30%	30%
Duty cycle	30%	30%	30%	30%	30%	30%
Back gauge	390 mm	640 mm	640 mm	640 mm	640 mm	640 mm
Foot switch	standard	standard	standard	standard	standard	standard
Nominal	4 Amp	6 Amp	6 Amp	12 Amp	15 Amp	15 Amp
Protection	Thermal cut-out 70°C			Thermal cut-out 70°C		
Bending edge length	670 mm	1050 mm	1300 mm	2090 mm	2590 mm	3290 mm
Distance between	630 mm	1010 mm	1260 mm	2028 mm	2528 mm	3228 mm
Packing size	83x112x38 cm	120x112x38 cm	145x112x38 cm	220x112x38 cm	270x112x38 cm	370x112x38 cm
N.W./G.W.	102/127 kg	142/177 kg	185/241 kg	259/350 kg	290/403 kg	381/507 kg



## Folding Machine

Model	PBB1020/2.5	PBB1270/2	PBB1520/1.5	PBB2020/1.2	PBB2520/1.0
Max. working length	1020 mm	1270 mm	1520 mm	2020 mm	2520 mm
Max. sheet thickness	2.5 mm	2.0 mm	1.5 mm	1.2 mm	1.0 mm
Max. clamping bar	47 mm	47 mm	47 mm	47 mm	47 mm
Folding angle	0-135°	0-135°	0-135°	0-135°	0-135°
Packing size	139x56x128 cm	164x58x128 cm	189x63x128 cm	240x66x130 cm	292x94x130 cm
N.W. / G.W.	290/355 kg	340/420 kg	390/480 kg	540/655 kg	590/770 kg



## Fodina Machine

Model	PBB1020/2A	PBB1270/2A	PBB1520/1.5	PBB1020/3SH	PBB1270/3SH	PBB2020/3SH
Max. working length	1020 mm	1270 mm	1520 mm	1020 mm	1270 mm	2020 mm
Max. sheet thickness	2.0 mm	2.0 mm	1.5 mm	2.0 mm	1.5 mm	1.0mm
Max. clamping bar	47 mm	47 mm	47 mm	47 mm	47 mm	47 mm
Folding angle	0-135°	0-135°	0-135°	0-150°	0-150°	0-150°
Packing size	139x56x128 cm	164x58x128 cm	189x63x128 cm	139x56x130 cm	164x63x130 cm	240x66x130 cm
N.W. / G.W.	325/390 kg	370/450 kg	395/466 kg	360/430 kg	420/505 kg	590/659 kg



## Hydraulic Folding

Model	W62Y-3X2500	W62Y-4X3100	W62Y-4X2500	W62Y-5X2500	W62Y-5X3100
Max. sheet thickness(mm)	3	4	4	5	5
Max. working length (mm)	2500	3100	2500	2500	3100
Folding	120°	120°	120°	120°	120°
Max. clamping bar	110	110	110	110	110
Motor Model	Y112-M-4 B3	Y112-M-4 B3	Y112-M-4 B3	Y112-M-4 B3	Y112-M-4 B3
Motor power(kw)	4	5	4	5	5
Oil Pump	PVL1-14	PVL1-14	PVL1-14	PVL1-14	PVL1-14
Flow(L/r)	14.1	14.1	14.1	14.1	14.1
Pressure	21	21	21	21	21
Packing size(cm)	340x164x185	400x164x185	340x164x185	340x164x185	400x164x185



## Hydraulic Folding

Model	HW1220x3.5	HW1830x3.5	HW2440x3.5	HW3050x3.5
Max. bending thickness	3.5 mm (stainless steel 2.5 mm)	3.5 mm (stainless steel 2.5 mm)	3.5 mm (stainless steel 2.5 mm)	3.5 mm (stainless steel 2.5 mm)
Max. bending width	1220 mm	1830 mm	2440 mm	3050 mm
Bending	0-135°	0-135°	0-135°	0-135°
Max. box	150 mm	150 mm	150 mm	150 mm
Large beam opening	75 mm	75 mm	75 mm	75 mm
Manual back gauge	660 mm	660 mm	660 mm	660 mm
Hydraulic cylinder pressure	Max. 15 Mp	Max. 15 Mp	Max. 15 Mp	Max. 15 Mp
Hydraulic cylinder speed	50-85 mm/s	50-85 mm/s	50-85 mm/s	50-75 mm/s
Motor working	12 Mp	12 Mp	9-13 Mp	16 Mp
Manual beam adjustment (front and	0-25 mm	0-25 mm	0-25 mm	0-25 mm
Control panel A	with movable control panel	with movable control panel	with movable control panel	with movable control panel
Control panel B	with fixed control panel	with fixed control panel	with fixed control panel	with fixed control panel
Motor power	3.7 kW	3.7 kW	5.5 kW	7.5 kW
Packing size	205x102x170 cm	265x102x170 cm	325x102x170 cm	390x102x170 cm
N.W./G.W.	1780/1880 kg	2170/2300 kg	2850/3000 kg	3400/3525 kg



## Electric Folding

Model	EFMS2020	EFMS2520	EFMS3020
Max. bending width	2020 mm / 80"	2520 mm / 100"	3020 mm / 120"
Max. bending thickness	1.5 mm / 16Ga	1.0 mm / 20 Ga	1.0 mm / 20 Ga
Bending angle	0-135°	0-135°	0-135°
Opening Height	100 mm / 4"	100 mm / 4"	100 mm / 4"
Motor pressing	0.37 kW / 0.50HP	0.37 kW / 0.50HP	0.37 kW / 0.50HP
Motor folding	0.75 kW / 1HP	0.75 kW / 1HP	0.75 kW / 1HP
Packing size	283x76x142 cm	333x76x141 cm	383x76x145 cm
N.W./G.W.	965/1140 kg / 2127/2513 lbs	1310/1620 kg / 2890/3575 lbs	1630/1930 kg / 3598/4260 lbs



## Slip Roll Machine

Model	W01-0.8X305	W01-0.8X610	W01-0.8X915	W01-0.8X1000	W01-1.5X1300	W01-2X1000	W01-2X1250	W01-1.5X1550	W01-0.8X2050
Max thickness s (mm)	0.8	0.8	0.8	0.8	1.5	2	2	1.5	0.8
Max width (mm)	305	610	915	1000	1300	1000	1250	1550	2050
Dia.of roll(mm)	25.4	38	50	50	75	60	60	60	60
Packing dimension	54X24X28	95X27X38	134X34X50	148X35X50	170X43X56	147X39X67	171X39X67	203X39X67	252X39X67
N.W./G.W.(kg)	13/14	37/40	80/90	86/107	195/220	200/240	223/260	200/240	290/380



## Electric Slip Roll

Model	ESR-1300X1.5	ESR-1300X1.5E	ESR-1300X2.5	ESR-1300X4.5	ESR-1300X6.5	ESR-1550X3.5	ESR-2070X2.5	ESR-2070X3.5	ESR-3050X3.5E	HER-2070X6.5
Max.rolling thickness(m m)	1.5 mm	1.5 mm	2.5	4.5	6.5	3.5	2.5	3.5	3.5 mm	6.5 mm
Max.rolling width(mm)	1300 mm	1300 mm	1300	1300	1300	1550	2070	2070	3010 mm	2070 mm
Dia.of roller(mm)	75 mm	60 mm	90	120	150	120	120	127	170 mm	191 mm
Min. rolling Dia. (mm)	85	70	100	130	170	130	130	140	190 mm	215 mm
Motor power(kw)	0.75 kW/3HP	0.75 kW/3HP	1.5	2.2	3	2.2	2.2	3	5.5 kW	4 kW
Packing size	182x53x116cm	186x55x116cm	186x68x121cm	192x68x121cm	192x70x121cm	216x70x121cm	262x70x121cm	266x70x121cm	372x70x121cm	311x107x138cm
N.W./G.W.	280/340kg	270/340kg	640/600kg	750/830kg	1100/1190kg	840/935kg	1060/1200kg	1110/1250kg	1968/2248kg	3110/3300 kg



## Universal Bender

Model	UB-70	UB-100	UB-100A	SBG-30	SBG-40
Capacity	Flat steel 70x10 mm	100x10 mm	100x7 mm	30x10 mm	30x8 mm
	Round steel 20 mm	20 mm	22 mm	10 mm	15 mm
	Square steel 18x18mm	18x18mm	20x20mm	10x10mm	13x13mm
	Angle steel 60x8/70x15 mm	60x8/100x12 mm	-	-	-
Packing size	Body 39x29x28 cm	39x29x28 cm	55x32x24 cm	55x30x22 cm	50x32x23 cm
	Handle 72x18x13 cm (20 pc)	72x18x13 cm (20 pc)	Together with body	Together with body	Together with body
N.W./G.W.	28/29kg	31/32kg	34/36 kg	27/29kg	23/24kg







Round Bending Machine

Model	RBM30HV	RBM40HV	HRBM40HV	RBM50HV	HRBM50HV	HRBM65HV	HRBM80HV	HRBM100HV	W24Y-1000
Dia. Of roller	φ 30mm	φ 40 mm	φ 40 mm	φ 50 mm	φ 50 mm	φ 65 mm	φ 80mm	φ 100mm	φ 75mm
Power	0.75kw/1HP	1.5kw/2HP	1.5kw/2HP	2.2kw/3HP	2.2kw/3HP	2.2kw/3HP	2.2kw/3HP	2.2kw/3HP	4kw/3kw
Spindle speed	9r/min	9.3r/min	9.3r/min	13r/min	13r/min	9.3r/min	9.3r/min	9.3r/min	9.3r/min
Packing Size	120x75x121cm	117x85x156cm	117x85x185cm	102x83x156cm	103x83x180 cm	119x115x180cm	120x115x180cm	120x115x180cm	147x122x171cm
N.W./G.W.	244/282kgs	425/495KGS	490/586KGS	450/582KGS	515/647KGS	720/920KGS	830/970KGS	896/1040KGS	1660/1760

Bead Roller Machine

Model	RM08	RM12	RM18	RM24M	RM36	RM42
Capacity	0.8mm/22Ga	1.2mm/18Ga	1.2mm/18Ga	1.0 mm /20 Ga	1.0 mm /20 Ga	1.0 mm /20 Ga
Throat Depth	177mm/7"	305mm/12"	457mm/18"	610mm/24"	910mm/36"	1067mm/42"
Packing (cm)	50x45x16	38x45x16	73x27x14	90x65x40 cm	157x57x55 cm	165x80x40 cm
N.W./G.W.	22/24kg	19/21 kg	24/26 kg	55/60 kg	74/90 kg	87/95 kg
	48/53lb	42/46 lbs	53/57 lbs	121/132 lbs	163/198 lbs	192/210 lbs



Electric Bead Roller Machine

Model	TB-12	ETB-12	ETB-25	ETB-40	RM18E
Thickness max	1.2mm/ 18Ga	1.2mm/ 18Ga	2.5mm/ 12Ga	4mm/ 8Ga	1.8mm/ 15Ga
Cylinder	140mm/ 5	140mm/ 5	120mm/ 4	165mm/ 6 1/2"	238mm/ 9 3/8"
Throat depth	200mm/ 8"	200mm/ 8"	280mm/ 11"	300mm/ 12"	-
Cylinder	-	32 rpm	20 rpm	15.3 rpm	-
Motor Power	-	0.75kW/ 1HP	1.5kW/ 2HP	2.2Kw/ 3HP	1.5KW
Packing size	67X32X60 cm	110X48X148 cm	147X58X135 cm	165X58X140 cm	88X53X123 cm
Net weight	48 kg/ 106lbs	120 kg/	235 kg/	341 kg/ 752lbs	140kg/ 171 lbs



Hand Pipe Bender

Model	YP9	YP38	UBM30	RB-1	RB-2	TB-3	HTB-1000
Max. bending angle	200°	200°	200°	270°	180°	120°	120° /240°
Packing size	67 x 26 x 13C	88 x 26 x 26C	88 x 26 x 26C	103X43X35CM	110X40X40CM	98x34x36cm	140x 70 x 116 cm
N.W./G.W.	17/18KG	22/24KG	31/ 32 kg	56/71KG	51/61KG	64/67KG	102 / 154 kg



Shrinker & Stretcher

Model	SS-18	SS-18FD	SS-16	SS-16F	FSM-16
Capacity (m m)	1.2	1.2	1.5	1.5	1.5
Throat Depth (mm)	25.4	25.4	208	208	152
Packing size (cm)	46 x 20 x 13	113 x 43 x 17	35 x 17 x 40	97 x 64 x 26	118 x 50 x 21
N.W/G W	5.5 / 5.8	24 / 26	24 / 26	29 / 30	38 / 50



English Wheel/Planishing Hammer

Model	F1.2X560	F1.2X710	F1.2X1000	PPH-500	PPH-610
Capacity	1.2mm/18Ga	1.2mm / 18Ga	1.2mm / 18ga	1.2mm / 18ga	1.5mm/16Ga
Throat Depth	560mm/22"	710mm /28"	1040mm / 40"	500mm / 20"	610mm / 24"
Packing size	84x74x34cm	89x80x27cm	183x93x35cm	75 x 73 x23 cm	173 x 94 x40 cm
N.W/G.W (kg)	62 /81kg	77 / 81 kg	144 /191kg	23 / 26 kg	79 / 125 kg



## Tube Pipe Roller Bender

Model	TR-40	Model	ETR-50	Model	TR-60
Min R	180 mm	Capacity round /square tube	2"	Capacity round /square tube	2"
Min D	450 mm	Capacity round pipe	1 1/2"	Capacity round pipe	1 1/2"
Packing size	57x 26x 40	Packing size	70x 56x 43	Packing size	62x 37x 23 cm
N.W./G.W.	19 / 21 kg	N.W./G.W.	57 / 71 kg	N.W./G.W.	32 / 33 kg



## Hand Brake

Model	BDS-4	BDS-5	BDS-6	BDS-8
Capacity	100 mm	125 mm	150 mm	200 mm
Width	2.0 mm	2.0 mm	2.0 mm	2.0 mm
Packing size	51x25x15 cm (20 pcs)	51x30x15 cm (20 pcs)	51x35x15 cm (20 pcs)	28x24x22 cm (10 pcs)
Net weight	21/22 kg	30/31 kg	42/43 kg	26/27 kg

## Universal Bender

Model	W-1	W-2
Packing size	107x31x32cm	107x41x26cm
N.W./G.W.	12/13kg	32/34kg



## Hand Brake

Model	W1.2x460	W1.2x630	W1.2x760	W1.2X915	W1.2X1000	W1.0X1220
Width	460 mm	630	760 mm	915	1000	1220
Thickness	1.2 mm	1.2mm	1.2 mm	1.2 mm	1.2 mm	1.0 mm
Angle	0-90°	0-90°	0-90°	0-90°	0-90°	0-90°
Packing size	50x19x12cm	67x19x12cm	80x17x12cm	97x19x12cm	110x19x14cm	131x19x14cm
N.W. / G.W.	4.5/5 kg	10/11kg	14/15 kg	19/21kg	26/29kg	33/36kg



## Arbor Press

Model	AP-1/2	AP-1	AP-2	AP-3	AP-5	AP-8	RAP-3	RAP-5
Capacity(ton)	1/2	1	2	3	5	8	3	5
Max Height& Dia(mm)	90x80	110X110	180x123	285x163	400x226	450x255	285x163	400x226
Largest arbor(mm)	26	29	40	44	70	65	44	70
Table Size(mm)	ø 95	ø 120	ø 155	ø 185	ø 255	ø 255	ø 185	ø 255
Ram square(mm)	19x19	25X25	32x32	38x38	50x50	60x55	38x38	50x50
Press	280	355	445	615	815	650	615	815
Base	240x170	268x1190	432x260	455x300	645x176	640x255	455x300	645x176
Packing size(cm)	27x12x29	46x19x48	46x23x61	76x37x95	65x27x82	46x23x61	76x37x95	
N.W./G.W(kg)	7 / 8	30/31	45/47	118/129	130/133	63/65	153/176	

## Round Bending Machine

Model	PR-3
Dia. Of Roller(mm)	32
Round steel capacity	6.5
Flat steel capacity	25X4
Handle length (mm)	320
Packing dimension	36X20X21
N.W./G.W.(kg)	6/7

## Tube Notcher

Model	PN-1/2S	PN-1/2A	PN-1/2H	PNM 1/2"
Tubing Capacity	2"	2"	2"	3"
Spindle	3/4"	3/4"	3/4"	
Spindle Adopter	1/2" to 5/8"	1/2" to 5/8"	1/2" to 5/8"	3/4" to 3" OD
Angle adjustment	0-60°	0-45°	0-50°	50°
Packing dimension	30X18X20 cm	30X18X14 cm	31X18X13 cm	31x16x14 cm
N.W./G.W.	4.5/5 kg	2.8/3 kg	4.1/4.6 kg	9.6 / 10.5 kg



## Pipe Notcher

Model	RA-1	RA-2	RA-3	PTN 12U
Tubing Capacity	1/4", 3/8", 1/2"	3/4", 1", 1 1/4"	1 1/2", 2"	1/4"-2"
Packing dimension	51 X 19X17 cm	51 X 19X17 cm	51 X 19X17 cm	86 X 45 X48 cm
N.W./G.W.	6.5/7.5 kg	8/9 kg	15/16 kg	98/112 kg



## Belt Drive Band Saw

Model	BS-712N	BS-712GR	BS-912B	BS-916B	BS-1018B
Cut Circular @90°	178mm(7")	178mm(7")	229mm(9")	229mm (9")	254mm (10")
Cut Rectangular @90°	178x305mm(7"x12")	178x210mm(7"x8.25")	178x305mm(7"x12")	127x405mm(5"x16")	127x457mm(5"x18")
Cut Circular @45°	127mm(5")	127mm(5")	150mm(6")	229mm (9")	150mm (6")
Cut Rectangular @45°	120x125mm(4.75"x4.88")	85x140mm(3.33"x5.5")	127x150mm(5"x6")	150x190mm(6"x7.5")	150x190mm(6"x7.5")
Blade speed @60Hz	27,41,59,78 MPM	34, 70, 104 MPM	32, 60, 88, 115 MPM	114, 196, 288, 377 FPM	35, 60, 88, 115 MPM
Blade speed @50Hz	22,34,49,64 MPM	29, 59, 87 MPM	26, 50, 73, 95 MPM	95, 164, 240, 312 FPM	29, 50, 73, 95 MPM
Blade size	20x0.9x2362 mm	20x0.9x2362 mm	27x0.9x2655mm	27x0.9x3090mm	27x0.9x3280mm
Motor power	750W 1HP(3PH), 1.1KW	750W 1HP(3PH), 1.1KW	1.1 kW 1.5HP(3PH), 1.1KW	1.5kW 2.0HP (3PH)	1.5kW 2.0HP (3PH)
Drive	V-belt	V-belt	V-belt	V-belt	V-belt
Packing size	125x51x115cm	132x77x115cm	154x59x115cm	172x83x114 cm	182x83x116 cm
N.W./G.W.	140/180kg	175/197 kg	190/252kg	280/340kg	310/392 kg